

2014 WERS Certified Products Directory Commercial
- AFRC



NOTES

1. Uw is the whole window U-value
2. SHGCw is the whole window solar heat gain coefficient
3. Tvw is the whole window visible (light) transmittance
4. Maximum air infiltration is 5.0L/s.m2 at a positive pressure difference of 75 Pa as measured according to AS 2047
5. Static performance (Uw SHGCw Tvw Tdw) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
6. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
7. Ratings for use with Section J of the Building Code of Australia - Class 2-9



Alspec Updated 12-Dec-16		Total Window - AFRC			
Window ID	Glazing	Uw	SHGC	Tvw	Air Inf
76mm ViewMax Sliding Window - Double Glazed					
ALS-003-01	4Clr/8/4Clr	4.1	0.60	0.64	0.07
ALS-003-02	4Clr/8/4EA	3.6	0.56	0.58	0.07
ALS-003-04	5EG/8/4Clr	4.1	0.39	0.52	0.07
ALS-003-05	6TS21/6/4	4.1	0.19	0.13	0.07
ALS-003-06	6TS21/6/4EA	3.8	0.17	0.12	0.07
ALS-003-07	LB ClrSI 6.38/6/4	3.4	0.44	0.61	0.07
ALS-003-08	LB GySI 6.38/6/4	3.4	0.30	0.29	0.07
ALS-003-09	LB ClrPrvSI 6.38/6/4	3.4	0.36	0.46	0.07
ALS-003-10	LB ClrS0 5/6/5	3.4	0.47	0.62	0.07
ALS-003-11	LB GyS0 5/6/5	3.4	0.31	0.33	0.07
ALS-003-12	LB ClrS0 4/8/4	3.2	0.47	0.63	0.07
ALS-003-13	LB GyS0 4/8/4	3.2	0.34	0.39	0.07
76mm ViewMax Sliding Window - Single Glazed					
ALS-004-01	4Clr	6.5	0.69	0.71	0.07
ALS-004-02	6.38CPClr	4.7	0.56	0.65	0.07
ALS-004-03	6.38CPGn	4.7	0.41	0.56	0.07
ALS-004-04	6.38CPNtrl	4.7	0.42	0.47	0.07
ALS-004-05	6.38Lam	6.3	0.64	0.70	0.07
ALS-004-06	6AB	6.4	0.47	0.42	0.07
ALS-004-07	6EcAdBz	4.9	0.37	0.30	0.07
ALS-004-08	6EcAd	4.9	0.51	0.53	0.07
ALS-004-09	6EcAdEG	4.9	0.35	0.38	0.07
ALS-004-10	6EcAdGy	4.9	0.38	0.25	0.07
ALS-004-11	6EcAdAB	4.9	0.30	0.31	0.07
ALS-004-12	6EG	6.4	0.43	0.52	0.07
ALS-004-13	6SpGy	6.4	0.29	0.07	0.07
101.6 ViewMax Sliding Window - Double Glazed					
ALS-007-01	4Clr/8/4Clr	4.4	0.58	0.61	0.09
ALS-007-02	4Clr/8/4EA	3.9	0.54	0.56	0.09
ALS-007-03	5EG/8/4Clr	4.4	0.37	0.50	0.09
ALS-007-04	5EG/8/4EA	3.9	0.33	0.46	0.09
ALS-007-05	6TS21/6/4	4.4	0.18	0.12	0.09
ALS-007-06	6TS21/6/4EA	4.1	0.16	0.11	0.09
ALS-007-07	6EVGy/6/4Clr	4.2	0.29	0.22	0.09
ALS-007-08	LB ClrSI 6.38/6/4	3.7	0.43	0.59	0.09
ALS-007-09	LB GySI 6.38/6/4	3.7	0.29	0.28	0.09
ALS-007-10	LB ClrPrvSI 6.38/6/4	3.7	0.35	0.44	0.09
ALS-007-11	LB ClrS0 5/6/5	3.7	0.45	0.59	0.09
ALS-007-12	LB GyS0 5/6/5	3.7	0.30	0.32	0.09
ALS-007-13	LB ClrS0 4/8/4	3.5	0.46	0.60	0.09
ALS-007-14	LB GyS0 4/8/4	3.5	0.33	0.37	0.09
101.6 ViewMax Sliding Window - Single Glazed					
ALS-008-01	4Clr	6.6	0.67	0.69	0.09
ALS-008-02	6.38CPClr	4.8	0.54	0.63	0.09
ALS-008-03	6.38CPGn	4.8	0.40	0.55	0.09
ALS-008-04	6.38CPGy	4.8	0.40	0.30	0.09
ALS-008-05	6.38CPNtrl	4.9	0.41	0.45	0.09

ALS-008-06	6.38Lam	6.4	0.63	0.68	0.09
ALS-008-07	6AB	6.5	0.41	0.41	0.09
ALS-008-08	6EcAd	5.0	0.49	0.51	0.09
ALS-008-09	6EcAdBIGn	5.0	0.36	0.44	0.09
ALS-008-10	6EcAdBz	5.0	0.36	0.29	0.09
ALS-008-11	6EcAdEAB	5.0	0.29	0.30	0.09
ALS-008-12	6ECAdEG	5.0	0.29	0.37	0.09
ALS-008-13	6EcAdGy	5.0	0.33	0.25	0.09
ALS-008-14	6EG	6.5	0.41	0.51	0.09
ALS-008-15	6SpGy	6.5	0.28	0.07	0.09
ALS-008-16	10.38GyLam	6.4	0.53	0.36	0.09
ALS-008-17	6.38GyLam	6.5	0.56	0.37	0.09
ALS-008-18	6Gy	6.5	0.53	0.36	0.09